



NPX

ELECTRIC 24/36 VOLT
3000 / 3500 / 4000 / 4500 lbs.
(1350 / 1600 / 1800 / 2000 kg)

STANDARD SPECIFICATIONS

15D/17/20/22

Manufacturer's Designation		NPX 15D	NPX 17	NPX 20	NPX 22
Load Capacity / Rated Load @ 24" LC	lbs(kg)	3000 (1350)	3500 (1600)	4000 (1800)	4500 (2000)
Height Overhead Guard	in(mm)	95 (2413)	95 (2413)	95 (2413)	95 (2413)
Frame Width	in(mm)	40.25 (1022)	40.25 (1022)	40.25 (1022)	40.25 (1022)
Right Angle Stack (48"L x 40"W, Add 8" for Clearance)	in(mm)	116 (2940)	102 (2602)	102 (2602)	109 (2776)
Outside Turning Radius	in(mm)	76.14 (1934)	66.5 (1689)	66.5 (1689)	69.7 (1770)
Travel Speed Unloaded	mph (kph)	7.5/7.5 (12.0/12.0)	7.5 (12.0)	7.5 (12.0)	7.5/7.5 (12.0/12.0)
Power Unit		36 volt	Dual 24 volt / 36 volt	Dual 24 volt / 36 volt	36 volt

STANDARD FEATURES

- Key Switch • Load Backrest Extension • Electronic Horn • Rear Overhead Guard Post Protection
- Heavy Duty Battery Rollers • Battery Retainers • Lever Type Battery Connect-Disconnect • Metal Capacity Plate



For more information on this model and full line of CLARK Forklifts, find your local CLARK Dealer at www.clarkmhc.com