#### Issue 08/17

### HÜDIG Generator

## STEP 60 Kompakt 24





#### General technical data, approx .:

Length:	2800 mm
Width:	1200 mm
Height:	1655 mm
Weight (dry):	1780 kg
Tank volume:	373
Tank volume sufficient for:	24 h
Sound power level:	91 dB
calculated sound pressure level:	$LPA_{7m}=64 \text{ dB}(A)$
	$LPA_{10m}=62 dB(A)$

#### Generator:

Brand:	Mecc Alte
Type:	ECO 32-2 L/4
Apparent power:	60 kVA
3 ~ cos φ:	0,8
Voltage 3 ~:	400 V
Voltage 1~:	230 V
Frequency:	50 Hz
Current 3 ~:	87 A
Overload:	10% of the rated output
	every 6 h for 1 h
Protection class:	IP 21

Protection class:

#### Motor:

**IVECO** Brand: Type: N45SM1F Emission class: IIIA Number of cylinders: 4 Output (PRP): 56.3 kW 1500 min<sup>-1</sup> Speed: Fuel: Diesel Fuel consumption: at 100% load: 16,7l/h at 50% load: 9,5 l/h

#### Electrical connection via sockets:

1 x shockproof socket 230V 2 x CEE socket, 5-pole, 32 A, 400 V 1 x CEE socket, 5-pole, 63 A, 400 V All sockets are protected with a 30 mA earth leakage circuit breaker (RCD).

#### Features

Technical Data

Emergeny stop button Operation via central control panel Voltmeter Amperemeter Frequency display Operating hours counter Fuel shortage signal (reserve) Electronic voltage regulator Motor automatic switch-off: - excessive temperature - oil pressure lack - fuel shortage - cooling water shortage Lockable doors Lifting holes for forklift trucks Central crane lugs Integrated emission sound absorber Closed oil drip pan

#### **Optional Accessories**

Double-walled tank Emergency automatic standy-by Mains switching for automatic standy-by with - 3-phase monitoring in stand-by - Battery charger Tank display Engine preheating 80 km/h chassis - Truck or - Car traction device mounted - Including TÜV testing Earth rod Universal current sensitive FI circuit breaker Paint finish in customer's colour Connection for external additional tank Further accessories on request

Subject to technical modifications

# HÜDIG – Ihr Partner, der für Sie durchs Wasser geht



Absenk- und Beregnungsanlagen Heinrich-Hüdig-Straße 2 · 29227 Celle Telefon (0 51 41) 88 45-0 · Fax (0 51 41) 8 69 18 e-mail: Info@huedig.de